

SPOJNI KOMAD S PRIRUBNICOM
EINFLANSCHSTÜCKE
FLANGED SPIGOT PIECES

F

Art N°
701

Standardna površinska zaštita: plastificirano min. 250 mic RAL 5015


Standard beschichtung: Pulverbeschichted min. 250 mic RAL 5015

Standard coating: Fusion bonded epoxy powder min. 250 mic RAL 5015

Prirubnice prema EN 1092-2 ili na zahtjev prema ostalim standardima.

Einbauf lansche nach EN 1092-2 oder auf Anfrage nach andere Standard.

Flanges according to EN 1092-2 or on request according to other standard.



EN 545



RAL GSK
 GSK-ID: 1238



Nazivni promjer Nennweite Nominal size DN	L	d	Masa Gewicht Weight (kg)	
			PN 10	PN 16
40	335	56	6	
50	340	66	7,5	
60	345	77	7,6	
65	345	82	7,6	
80	350	98	7,8	
100	360	118	9,7	
125	370	144	12,5	
150	380	170	15,8	
200	400	222	22,8	
250	420	274	31,8	35,8
300	440	326	43,3	47,7
350	460	378	52,3	55,3
400	480	429	64,3	70,3
450	500	480	82,1	92,3
500	520	532	93,9	108,9
600	560	635	135	159
700	600	738	179	198
800	600	842	239	250
900	600	945	287	298
1000	600	1048	354	376
1100	600	1152	400	435
1200	600	1255	469	526